



Products

Merluza 6x36 Class

- Steel Core
- Galvanized
- 6x31WS
- 6x36WS
- 6x41WS
- 6x43SWS
- 6x49SWS




6x31WS




6x36WS



6x41WS



6x43SWS



6x49SWS

6x36 Class Steel Core Strength & Weights Chart (inches)

Diameter (in)	Approx. Weight (lb/ft)	Minimum Breaking Force (lbs.)	
		IPS	EIP
1/4	0.12	5,890	6,790
5/16	0.18	9,150	10,540
3/8	0.26	13,120	15,100
7/16	0.35	17,780	20,380
1/2	0.46	23,000	26,600
9/16	0.59	29,000	33,600
5/8	0.72	35,800	41,200
3/4	1.04	51,200	58,800
7/8	1.42	69,200	79,600
1	1.85	89,800	103,400
1 1/8	2.34	113,000	130,000
1 1/4	2.89	138,800	159,800
1 3/8	3.50	167,000	192,000
1 1/2	4.16	197,800	228,000
1 5/8	4.88	230,000	264,000
1 3/4	5.67	266,000	306,000
1 7/8	6.50	304,000	348,000
2	7.39	344,000	396,000
2 1/8	8.35	384,000	442,000
2 1/4	9.36	430,000	494,000
2 3/8	10.40	478,000	548,000
2 1/2	11.60	524,000	604,000
2 5/8	12.80	576,000	658,000
2 3/4	14.00	628,000	736,000
2 7/8	15.30	682,000	796,000
3	16.60	740,000	856,000
3 1/8	18.00	798,000	920,000
3 1/4	19.50	858,000	984,000
3 3/8	21.00	918,000	1,074,000
3 1/2	22.70	982,000	1,144,000
3 3/4	26.00	1,114,000	1,290,000
4	29.60	1,254,000	1,466,000

Reference Specifications: ASTM-A-1023; API 9A

6x36 Class Steel Core Strength & Weights Chart (millimeters)

Diameter (mm)	Approx. Weight (kg/m)	Minimum Breaking Force (Metric Tons)
---------------	-----------------------	--------------------------------------

		IPS	EIP
6.35	0.18	2.7	3.1
7.94	0.27	4.1	4.8
9.53	0.39	6.0	6.9
11.1	0.52	8.1	9.2
13	0.68	10.4	12.1
14.5	0.88	13.2	15.2
16	1.07	16.2	18.7
19	1.55	23.2	26.7
22	2.11	31.4	36.1
26	2.75	40.7	46.9
29	3.48	51.3	59.0
32	4.30	63.0	72.5
35	5.21	75.7	87.1
38	6.19	89.7	103.0
42	7.26	104.0	120.0
45	8.44	121.0	139.0
48	9.67	138.0	158.0
52	11.0	156.0	180.0
54	12.40	174.0	200.0
58	13.90	195.0	224.0
60	15.50	217.0	249.0
64	17.30	238.0	274.0
67	19.00	261.0	299.0
71	20.80	285.0	333.0
74	22.80	309.0	361.0
77	24.70	336.0	389.0
80	26.80	362.0	417.0
83	29.00	389.0	447.0
87	31.30	416.0	487.0
90	33.80	445.0	519.0
96	38.70	505.0	585.0
103	44.00	569.0	665.0
Reference Specifications: ASTM-A-1023; API 9A			