



Products

Elevador 8x19 Class

- Fiber Core
- Lift Rope Bright
- 8x19S
- 8x25F



8x19S



8x25F

8x19 Class Fiber Core Strength & Weights Chart (inches)

| Diameter (in) | Approx. Weight (lb/ft) | Minimum Breaking Force (lbs.) 1370 / 1770 N / mm ² / Dual Tensile |
|--|------------------------|---|
| 5/16 | 0.14 | 6,305 |
| 3/8 | 0.22 | 9,877 |
| 7/16 | 0.27 | 11,949 |
| 1/2 | 0.37 | 16,689 |
| 5/8 | 0.58 | 25,353 |
| 3/4 | 0.82 | 35,714 |
| Reference specification: BS 302 PART 4 | | |

8x19 Class Fiber Core Strength & Weights Chart (millimeters)

| Diameter (mm) | Approx. Weight (kg/m) | Minimum Breaking Force (Metric Tons) 1370 / 1770 N / mm ² / Dual Tensile |
|--|-----------------------|--|
| 8 | 0.213 | 2.86 |
| 10 | 0.328 | 4.48 |
| 11 | 0.408 | 5.42 |
| 13 | 0.555 | 7.57 |
| 16 | 0.856 | 11.5 |
| 19 | 1.220 | 16.2 |
| Reference specification: BS 302 PART 4 | | |